



TECHNICAL SPECIFICATIONS

Parameters	CCL6H	CCL12H	CCM6H	CCM12H	CCH6H	CCH12H
Camera	4 Nos	4Nos	8Nos	8Nos	16Nos	16Nos
DVR	1Nos	1Nos	1Nos	1Nos	1Nos	1Nos
Battery Backup	4 - 6 Hours	8 - 12 Hours	4 - 6 Hours	8 - 12 Hours	4 - 6 Hours	8 - 12 Hours
Input AC Voltage	160V - 260V	160V - 260V	160V - 260V	160V - 260V	160V - 260V	160V - 260V
Output DC Voltage	12V	12V	12V	12V	12V	12V
Camara Connecters	4 Nos	4 Nos	8Nos	8Nos	16Nos	16Nos
Input Indications	Green LED	Green LED	Green LED	Green LED	Green LED	Green LED
Output Indications	Yellow LED	Yellow LED	Yellow LED	Yellow LED	Yellow LED	Yellow LED
Trip Indication	Red LED	Red LED	Red LED	Red LED	Red LED	Red LED
Fuse Protection	Provided	Provided	Provided	Provided	Provided	Provided
Fuse Blow Indication	Red LED	Red LED	Red LED	Red LED	Red LED	Red LED
Audio Alarm	Provided	Provided	Provided	Provided	Provided	Provided

MFD BY

**CREATIVE TECHNOLOGIES, PRAGATI BUILDING
KINFRA INDUATRIAL PARK KORATTY,THRISSUR
PH : 04802733144,MOB : 9447053829.**