



# CREATIVE Technologies



## Technical Data 96VDC/40 Amps MPPT SOLAR CHARGER

### TECHNICAL SPECIFICATIOIS

(Specifications are subject to change without notice)

**CAPACITY - 96 VOLT 40 Amps**

Battery Voltage - 96 volt

Maximum Solar current - 40 Amps

Solar Panel Maximum - 4000 Watts

Maximum Open circuit voltage - 400 VDC

Battery Full charges - 118.4

Battery low warning - 84

### LCD INDICATION ( SOLAR PARAMETERS)

Battery voltage

Instataneous power

Power / unit from solar panel

Battery reserve capacity

### FEATURES

- ▶ Hybrid Duo Technology
- ▶ Multiple Microprocessor design
- ▶ LCD display for solar parameters
- ▶ Cost efficient battery bank
- ▶ High capacity Solar panel connectivity
- ▶ Panel Select
- ▶ Live loadability from solar panel
- ▶ Intelligent Solar Power Monitoring system
- ▶ Resetable Watt hour Meter for solar panel
- ▶ Over Load Protection
- ▶ Short circuit Protection
- ▶ Battery Over Charge Protection

SDF Pragati building, Kinfra Industrial Park, Kinfra Park P.O., Koratty, Thrissur, Kerala

[www.creativetechnologies.in](http://www.creativetechnologies.in), Email : [creative.ups@gmail.com](mailto:creative.ups@gmail.com)

Ph : 0480 2733144, 9447053829