



# CREATIVE Technologies



## 2 CHANNEL SMPS INDUSTRIAL BATTERY CHARGER (12V / 2A-10A)

### INPUT

Operating voltage.....140V-270VAC  
In put frequency .....47 - 55 Hz

### OUTPUT 1

Output voltage (Variable) .....10V - 16Vdc  
Output current (Variable) ..... 2 - 10Amps  
Output efficiency.....90%  
Output humidity.....0-90% Rh non condensing

### OUTPUT 2

Output voltage (Variable) .....10V - 16Vdc  
Output current (Variable) ..... 2 - 10Amps  
Output efficiency.....90%  
Output humidity.....0-90% Rh non condensing

### TYPE OF BATTERY

1. Tubular battery
2. Automotive battery
3. Sealed maintiance free battery (SMF)
4. Lithium Ion battery
5. Lithium ferro phosphate battery (LiFePO4)

### APPLICATIONS

- Car battery charging
- Generator battery charging
- Inverter battery charging
- Emergency light battery charging

### PROTECTION

- Battery over Charge
- Charging Current Limit
- Reverse polarity (Fuse)

### ENCLOSURE

Powder coated metal box

**WEIGHT : 3Kg**

**SIZE : 38\*23\*15 cm**

### WARRANTY

6 Months

SDF Pragati building, Kinfra Industrial Park, Kinfra Park P.O., Koratty, Thrissur, Kerala

www.creativetechnologies.in, Email : creative.ups@gmail.com, Ph : 0480 2733144, 9447053829