

CREATIVE Technologies



4 CHANNEL SMPS INDUSTRIAL BATTERY CHARGER (12V / 2A-10A)

INPUT

Operating voltage.....140V-270VAC
In put frequency47 - 55 Hz

OUTPUT 1

Output voltage (Variable)10V - 16Vdc
Output current (Variable) 2 - 10Amps
Output efficiency.....90%
Output humidity.....0-90% Rh non condensing

OUTPUT 2

Output voltage (Variable)10V - 16Vdc
Output current (Variable) 2 - 10Amps
Output efficiency.....90%
Output humidity.....0-90% Rh non condensing

OUTPUT 3

Output voltage (Variable)10V - 16Vdc
Output current (Variable) 2 - 10Amps
Output efficiency.....90%
Output humidity.....0-90% Rh non condensing

OUTPUT 4 (FOR MC BATTERY CHARGING)

Output voltage (Variable)10V - 16Vdc
Output current (Variable) 1 - 6Amps
Output efficiency.....90%
Output humidity.....0-90% Rh non condensing

TYPE OF BATTERY

1. Tubular battery
2. Automotive battery
3. Sealed maintiance free battery (SMF)
4. Lithium Ion battery
5. Lithium ferro phosphate battery (LiFePO4)

APPLICATIONS

- Car battery charging
- Generator battery charging
- Inverter battery charging
- Emergency light battery charging

PROTECTION

- Battery over Charge
- Charging Current Limit
- Reverse polarity (Fuse)

ENCLOSURE

Powder coated metal box

WEIGHT : 5 Kg

SIZE : 29*58*11 cm

WARRANTY

6 Months

SDF Pragati building, Kinfra Industrial Park, Kinfra Park P.O., Koratty, Thrissur, Kerala

www.creativetechnologies.in, Email : creative.ups@gmail.com, Ph : 0480 2733144, 9447053829